

## FEATURE

- Injection-molded thermoplastic ABS housing, UL 94V-0 flame rating.
- Innovative, easy installation in minutes.
- Suitable for wall mount applications.
- Universal J-box mounting pattern.
- 120V/277VAC Dual voltage operation.
- 2X12pcs ultra bright LED lamps heads for emergency mode.
- Built-in 3.6V1000mAh Nickel cadmium battery for minimum 90 minutes emergency operation. (JLEU1)
- Built-in 3.6V2000mAh Nickel cadmium battery for minimum 90 minutes emergency operation. (JLEU1RC, Remote capability up to 2W)
- Maximum 24 hours for full recharge time.
- Test switch and charge indicator.
- UL and cULus listed.
- 0° to 40° C indoor damp location listed.

## ORDERING INFORMATION

FAMILY	HOUSING COLOR	REMOTE CAPACITY
JLEU1	BLANK(WHITE)	BLANK(WITHOUT)
	B(BLACK)	RC(WITH REMOTE)

## PACKING INFORMATION

MODEL NO.	PACKING INFORMATION	WEIGHTS
JLEU1	43x32.5x38cm/6pcs	6.5/6kgs
JLEU1RC	43x32.5x38cm/6pcs	7/6kgs

## ELECTRICAL INFORMATION

MODEL	RATED VOLTAGE	INPUT CURRENT	INPUT WATT	LED TYPE	CHARGING TIME	EMERGENCY RUN TIME
JLEU1	120/277V	0.035/0.025A	3.5W	2X12Pcs Super bright Ø5 LED	24 Hrs	90 Mins
JLEU1RC	120/277V	0.035/0.025A	3.5W	2X12Pcs Super bright Ø5 LED+2W Remote Lamps	24 Hrs	90 Mins

FAMILY: **JLEU1**

NOTES:

TYPE: **DUAL HEAD EMERGENCY LIGHT**



CEC DOE FC

